


0.5W, Fixed input voltage, isolated & unregulated single output



Patent Protection RoHS

## FEATURES

- Continuous short-circuit protection
- Output voltage range(Typ):4.85~5.15V
- Operating temperature range: -40°C to +105°C
- Isolation voltage: 1.5K VDC
- Compact SIP/DIP package
- International standard pin-out

B\_S-W5R2 & B\_D-W5R2 series are specially designed for applications where an isolated voltage is required in a distributed power supply system. They are suitable for

1. Where the voltage of the input power supply is stable (voltage variation:  $\pm 10\%V_{in}$ );
2. Where isolation between input and output is necessary (isolation voltage  $\leq 1500VDC$ );
3. Where the output voltage regulation and the ripple & noise of the output voltage is not strictly required;
4. Typical application: digit circuit condition; normal low-frequency artificial circuit condition; relay drive circuit and data switching circuit condition, etc.

## Selection Guide

Part No.	Input Voltage (VDC)	Output		Efficiency (%Min./Typ.) @ Full Load	Max. Capacitive Load( $\mu F$ )
	Nominal (Range)	Output Voltage (VDC)	Output Current (mA)(Max./Min.)		
B0505D-W5R2	5 (4.5-5.5)	5	100/10	70/75	220
B0505S-W5R2		5	100/10	70/75	

## Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Current (full load / no-load)		--	134/15	--/30	mA
Reflected Ripple Current		--	30	--	mA
Surge Voltage (1sec. max.)		-0.7	--	9	VDC
Input Filter		Filter capacitor			
Hot Plug		Unavailable			

## Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy		See tolerance envelope graph (Fig. 1)			
Line Regulation	Input voltage change: $\pm 1\%$	--	--	$\pm 1.2$	--
Load Regulation	10%-100% load	--	7	15	%
Ripple & Noise*	20MHz bandwidth	--	50	120	mVp-p
Temperature Coefficient	Full load	--	$\pm 0.03$	--	%/°C
Short Circuit Protection		Continuous, self-recovery			

Note: \* Ripple and noise are measured by "parallel cable" method, please see DC-DC Converter Application Notes for specific operation;

## General Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Isolation Voltage	Input-output, with the test time of 1 minute and the leak current lower than 1mA	1500	--	--	VDC
Isolation Resistance	Input-output, isolation voltage 500VDC	1000	--	--	M $\Omega$
Isolation Capacitance	Input-output, 100KHz/0.1V	--	20	50	pF
Operating Temperature	Derating when operating temperature up to 85°C, (see Fig. 2)	-40	--	105	°C
Storage Temperature		-55	--	125	

Casing Temperature Rise	Ta=25°C, nominal input, full load output	--	10	--	°C
Pin Welding Resistance Temperature	Welding spot is 1.5mm away from the casing, 10 seconds	--	--	300	
Storage Humidity	Non-condensing	--	--	95	%RH
Switching Frequency	Full load, nominal input voltage	--	77	--	KHz
MTBF	MIL-HDFK-217F@25°C	3500	--	--	K hours

**Physical Specifications**

Casing Material	Black flame-retardant and heat-resistant plastic (UL94 V-0)				
Dimensions	B_S-W5R2 series	11.60*6.00*10.16 mm			
	B_D-W5R2 series	12.70*10.16*8.20 mm			
Weight	B_S-W5R2 series	1.3g(Typ.)			
	B_D-W5R2 series	1.8g(Typ.)			
Cooling Method	Free air convection				

**EMC Specifications**

EMI	CE	CISPR22/EN55022	CLASS B (see Fig. 4 for recommended circuit)		
	RE	CISPR22/EN55022	CLASS B (see Fig. 4 for recommended circuit)		
EMS	ESD	IEC/EN61000-4-2	Contact ±8KV perf. Criteria B		

**Product Characteristic Curve**




Fig. 1








Fig. 2






## Design Reference

### 1. Typical application circuit


If it is required to further reduce input and output ripple, a filter capacitor may be connected to the input and output terminals, see Fig.3. Moreover, choosing a suitable filter capacitor is very important, start-up problems may be caused if the capacitance is too large. Under the condition of safe and reliable operation, the recommended capacitive load values are shown in Table 1.



Recommended capacitive load value table (Table 1)

V <sub>in</sub> (VDC)	C <sub>in</sub> (μF)	V <sub>o</sub> (VDC)	C <sub>out</sub> (μF)
5	4.7	5	10

### 2. EMC solution-recommended circuit




Input voltage (VDC)		5
EMI	C1	4.7μF /50V
	C2	Refer to the C <sub>out</sub> in Fig.3
	LDM	6.8μH

### 3. Output load requirements


In order to ensure the converter can work reliably with high efficiency, the minimum load should not less than 10% rated load when it is used. If the needed power is indeed small, please parallel a resistor on the output side (The sum of the efficient power and resistor consumption power is not less than 10%).

4. For more information please find DC-DC converter application notes on [www.mornsun-power.com](http://www.mornsun-power.com)

Dimensions and Recommended Layout B\_S-W52



Dimensions and Recommended Layout B\_D-W52



Notes:

1. Packing information please refer to Product Packing Information which can be downloaded from [www.mornsun-power.com](http://www.mornsun-power.com). Packing bag number: 58200003(B\_S-1WR2), 58200011(B\_D-1WR2);
2. If the product is not operated within the required load range, the product performance cannot be guaranteed to comply with all parameters in the datasheet;
3. The maximum capacitive load offered were tested at input voltage range and full load;
4. Unless otherwise specified, parameters in this datasheet were measured under the conditions of  $T_a=25^{\circ}\text{C}$ , humidity<75%RH with nominal input voltage and rated output load;
5. All index testing methods in this datasheet are based on our Company's corporate standards;
6. We can provide product customization service, please contact our technicians directly for specific information;
7. Specifications are subject to change without prior notice.

MORNSUN Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Luogang District, Guangzhou, P. R. China  
Tel: 86-20-38601850-8801 Fax: 86-20-38601272 E-mail: info@mornsun.cn